

Model MoniTurb-S (MTS)



- **Low maintenance**
- **Calibration interval: typical 24 month**
- **Sight glass material: Sapphire**
- **Sight glass cleaning: Via cleaning jet probe**
- **Cleaning in place (CIP)**
- **Process connection: DIN, ANSI, SMS, NPT, APV, TH, ...**
- **Optional air purge connection: 4mm**

Description:

The turbidity sensor Model MoniTurb-S uses the principle of 90° side scattered light to detect particles in liquids. The transmitter model Messenger is required to use this sensor. The system has been designed for continuous operation with long life time. The side scatter principle shows a very high sensitivity against small particle sizes (< 0.3 µm) in the liquid. A ratio measurement of direct- / scatter light assure highly reliable and repeatable measurement results. Inaccuracies caused by product colour, lamp ageing or window coating will be compensated. Calibration can be done in multiple ranges and measurement units like EBC, ppm, mg/l, etc.. The sensors can be installed into almost any type of pipe. Process connection, pressure, temperature, gasket material, etc will be application specific. Optional cleaning jets will allow a cleaning of the sapphire windows in determined intervals.

Applications:

- Filtration control
- Product quality
- Water / Waste water

Operational areas:

- Chemical industry
- Petrochemical industry
- Power plants
- Brew & Beverage

Technical Data:

Line size:	DN 25 – DN 125 / ½" - 5"	Measurement range:	typical 0–1NTU, 0–500NTU
Process pressure:	PN16 / ANSI class 150	Reproducibility:	± 1 %
Process temperature:	maximum 140°C	Detector system:	Silica diodes
Sensor material:	1.4404 / 316L	Cleaning:	optional cleaning jet probe
Sight glass material:	Sapphire	Sterilization:	CIP (cleaning in place)
Gasket material:	application specific	optional hazardous area:	ATEX Zone I or Zone II
Protection class:	IP65 / NEMA 4X		